



Cathedral Stone® Products, Inc.

The leader in scientific masonry restoration

WHEN SUBMITTING MASONRY SAMPLES FOR JAHN MORTAR COLOR SELECTION, PLEASE PAY ATTENTION TO THE FOLLOWING:

- 1. TAKE SAMPLE(S):** Select locations that represent typical color and texture.
Send one sample for each color needed.
Color: **SEND A CLEANED SAMPLE, IF BUILDING WILL BE CLEANED.
The lab will not clean any samples.**
Texture: Send a tooled sample if patch will be tooled.
Sample size: No smaller than 2" x 2" - larger if possible (**No Powder!**)
- 2. MARK SAMPLE(S):** **The surface to be matched must be clearly indicated.**
- 3. COMPLETE SAMPLE INFORMATION FORM:** Project Manager or Architect must complete the attached form and return it. One form should be completed for each sample being sent. **We cannot begin to process your samples until we receive the form(s) and payment.**
- 4. SEND SAMPLE(S) AND FORM TO:** Cathedral Stone Products, Inc.
Attn: Color Lab
7266 Park Circle Drive
Hanover, MD 21076
Fax: (410) 782-9155

Allow 2 Weeks for Processing Jahn Color Samples

You Will Receive:

- One matching dry powder sample
 - One cured sample representing the final product color.
 - The dry powder should be mixed and applied on site (from the same location that sample was removed) as a color mock-up.
 - Directions for mixing, application, and curing are included or can be found on www.cathedralstone.com.
(The site-applied sample should match our finished laboratory sample)
- ❖ If necessary we will notify you if we determine that a Standard or Custom Jahn color matches your masonry sample.

Please note the following exceptions:

Terra Cotta – We will supply your choice of Standard color or custom match the surface color. In either case, the Jahn repair should be painted with CSP's terra cotta glazing system to prevent later intrusion.

Granite – It is not possible for us to match the multicolored appearance of granite. We will supply you with a suitable matching background color – the appropriate aggregate (granite dust, etc.) must be added on site to the surface of the damp Jahn mortar; up to 20% of aggregate may be added. It may be necessary to lightly wash the finished repair with a mild acetic acid (white vinegar) to expose the aggregate within one or two days.

Marble – The Jahn M120 Marble Repair Mortar will be supplied in a uniform color. If attempting to simulate veining, on site techniques must be developed, possibly using paint, stains or a darker Jahn mix applied in veins carved into the Jahn repair.

REV: Feb 2016



Cathedral Stone® Products, Inc.

The leader in scientific masonry restoration

SAMPLE INFORMATION: JAHN MORTAR COLOR MATCH

Please complete this form (one for each different sample) and include it when you send us your sample. Our lab requires this information to formulate a custom Jahn product. We cannot process your sample without it. **For all sample colors the lab fee will be required, and must be received before the color matching process will begin.** Thank you!

Bill to: _____

Ship To: _____

Phone: (_____) _____

FAX: (_____) _____

Contact: _____

Email: _____

If you would like to pay the lab fee by credit card, please complete the following:

Card Number: _____ Exp. Date: _____ ID Code: _____

Card Holder's Name: _____ Card Holder's Signature: _____

Building or Project Name: _____

Address: _____

Type of Masonry Requested: _____

(i.e.: Brownstone, Limestone, Brick, Terra Cotta, Precast, Pointing Mortar, etc.)

****Pointing Mortar, what type of stone is being repointed?** _____

Person in charge of color approval: _____

(Architect, Consultant, Owner?)

Company: _____

Address: _____

Phone: (_____) _____

Fax: (_____) _____

Please answer the following questions about your sample:

Surface to be matched? exposed fractured *(Please mark the sample on the side to be matched)*

Will the building be cleaned? yes no Has the sample been cleaned? yes no

Note: We do not clean samples, if the building has or will be cleaned, the sample to be matched must also be clean.

How will the patches be textured? (ex. smoothed, tooled, left alone) Explain: _____

Will the patches be: painted? sealed? left alone? (Circle applicable)

Are you patching steps, pavers or other traffic areas? yes no

For your sample, would you like:

Standard Jahn Mortar (\$40 each – 1qt)

Custom Jahn Mortar (\$81 each – 1qt)

How much do you anticipate needing: _____ sq. ft. @ _____ depth (or # of pails: _____) When: _____

Name of Authorized Installer: _____ Authorized Installer #: _____

Submitted by: *(Signature)* _____